


Advanced C-102 Semi-automatic Blood Coagulation Analyzer provides fast & accurate results with less reagent sample consumption.



Turbo-Densitometric Measuring Principle

Turbo-densitometric Principle uses Optical Method .

LED is used as a Source of light. A Light beam passes through the cuvette containing the Reagent & Plasma.

Change in the intensity of light transmitted is converted into an electric signal.

The cuvette containing stir bar is used. Stir bar mixes the reagent & plasma forming a small whirl. The whirl helps in detecting the smallest fibrin clot.

Stirring mechanism & Optical method together constitute the basic feature of turbo-densitometric measuring principle.

Convenient

- Small footprint
- Designed for low volume laboratories or as a backup for high workload
- Latest LED technology
- Pre-programmed parameters
- Light Protection cap, prevents stray light and dust.

Ease of Access

- Built in timer
- Auto-start Function
- On- screen real-time display of measuring seconds
- Prior Beeper during testing, provides accuracy & efficiency

Economically Reliable

- Less sample & reagent consumption compared to Manual method
- Short incubation time increases throughput of the system
- Built in Thermal Printer
- Environment friendly system with minimum use of accessories
- Less user maintenance

Parameters

- PT-Prothrombin Time
- APTT-Activated Partial Thromboplastin Time
- TT - Test Thrombin