

# MAGLUMI<sup>®</sup> X6

Fully-auto Chemiluminescence Immunoassay Analyzer



**Flexible CLIA Solution  
For Medium/High-volume Laboratory**



**Innovation Brings Revolution**

## **CORE TECHNOLOGY – X-TECH**

**Patented Pipetting  
Technology**

**Accurate Incubation  
Technology**

**Intelligent Washing  
Technology**


**High-efficiency  
Loading Design**

**Stable and Precise  
Measuring Technology**

**Pioneer in Optional  
Wash Liquid Preparation**

**Multiple Expansion  
Solutions**

**User-friendly with Easy-operation  
and Real-time Display**






## MAGLUMI® X6

Based on X-Tech, gives you more possibility

- Throughput: 450 T/H
- Throughput per unit area: up to 320 T/H/m<sup>2</sup>
- On board capability: 112/412 samples
- Reagent position: 30
- Walk-away tests: up to 2000 tests
- Cuvettes loading in one time: up to 2002




## Illustration






# Advanced Technology



## Patented Pipetting Technology

- A revolutionary pipetting volume from 10-280  $\mu$ l sampling volume
- Disposable filtered Tips avoid aerosol pollution, ensure no cross-contamination during the test
- Higher pipetting accuracy with low pipetting CV
- One pipetting for multiple test to save the costs



## Accurate Incubation Technology

- Single cuvette with five-sided heating at 37°C, ensuring accurate, quick and uniform incubation
- Incubating 243 cuvettes simultaneously
- Non-contact mixing with different modes before incubation, ensuring sufficient reaction.



## Intelligent Washing Technology

- Magnetic separation washing with 4-group independent units and non-contact vortex mixing can reduce non-specific binding
- Different mixing modes depending on different assays, ensuring a sufficient washing to improve sensitivity



## Stable and Precise Measuring Technology

- PMT with heating and cooling function, ensuring the detection precision
- Independent measuring room, avoiding light cross contamination



## Multiple Expansion Solution

- 112 sample positions, up to 412 sample positions with expansion
- Capable to link laboratory automation system
- Multiple X6 units can be connected



## Pioneer in Optional Wash Liquid Preparation


\*Two modes: Automatic or Manual

- Select Auto mode on the software, connect the X6 to the water purification system, ease your operational burden
- If water purification system is not available, the preparation can be done by manually mixing the wash liquid with pure water



## User-friendly Design

- Fully automated analyzer from sample to result
- Light indicator and intelligent UI makes operation visualized
- Integrated packaging of cuvettes designed avoids damaging the cuvette wall
- One-side operation saves your space
- Real-time display and light indicator realize convenient management of analyzer status
- Up to 2000 walk-away test to economize manpower



## High-efficiency Loading Design

- No-pause sample/reagent loading/unloading without interrupt the test
- RFID saves the information, saves your time
- All sample can be defined as STAT to be tested in priority
- Four kinds of pipetting error detection technologies reduce sampling error rate








## Top 10 Highlights of MAGLUMI® X6

- 1 Throughput up to 450 T/H — One of the highest throughput analyzer with the same size.
- 2 Flexible sample positions design, from 112 to 412 which just require small upgrading.
- 3 Dual-mode wash liquid preparation — Automatic or manual based on multiple scenarios.
- 4 No-pause sample loading/unloading design and STAT mode to avoid wasting your time.
- 5 Up to 2000 walk-away tests to avoid high frequency of manual intervention.
- 6 "One-side operations" design to save your working space.
- 7 Intelligent **SnibeLinker™** remote service solution to ensure the fast response.
- 8 **MAGLUMI®** reagent kits are compatible with all **MAGLUMI®** series analyzers.
- 9 Intelligent UI interface, user-friendly, easy and convenient operation.
- 10 Four key technology design of **MAGLUMI®** X6 guarantee accurate and reliable results

## MAGLUMI® X6 Reagent and Consumables



Reaction Cup



Disposable TIPS



Starter 1+2



Wash Concentrate



Tubing Cleaning Solution



Light Check

# Broad CLIA Test Menu with 211 Assays



## Thyroid

TSH (3rd Generation)  
T4  
T3  
FT4  
FT3  
Tg (Thyroglobulin)  
TGA (Anti-Tg)  
Anti-TPO  
TRAb  
TMA  
Rev T3  
T-Uptake

## Hepatic Fibrosis

HA  
PIIIP N-P  
C IV  
Laminin  
Cholyglycine  
GP73

## TORCH

Toxo IgG  
Toxo IgM  
Rubella IgG  
Rubella IgM  
CMV IgG  
CMV IgM  
HSV-1/2 IgG  
HSV-1/2 IgM  
HSV-1 IgG  
HSV-2 IgG  
\*HSV-2 IgM  
\*HSV-1 IgM  
\*Toxo IgG Avidity  
\*CMV IgG Avidity

## STAT-X™

\*hs-cTnI  
\*NT-proBNP  
\*Myoglobin  
\*D-Dimer  
\*PCT  
\*CRP

## EBV

EBV EA IgG  
EBV EA IgA  
EBV VCA IgG  
EBV VCA IgM  
EBV VCA IgA  
EBV NA IgG  
EBV NA IgA

## Inflammation Monitoring

CRP  
PCT (Procalcitonin)  
IL-6 (Interleukin 6)  
SAA (Serum Amyloid A)  
\*PCT (STAT)  
\*CRP (STAT)  
\*TNF-α

## Kidney Function

β<sub>2</sub>-MG  
Albumin  
\*NGAL

## Fertility

FSH  
LH  
HCG/β-HCG  
PRL (Prolactin)  
Estradiol  
Testosterone  
free Testosterone  
DHEA-S  
Progesterone  
free Estriol  
17-OH Progesterone  
AMH  
SHBG  
Androstenedione  
PIGF  
sFlt-1

## Autoimmune

Anti-CCP  
Anti-dsDNA IgG  
ANA Screen  
ENA Screen  
Anti-Sm IgG  
Anti-Rib-P IgG  
Anti-Scl-70 IgG  
Anti-Centromeres IgG  
Anti-Jo-1 IgG  
Anti-M2-3E IgG  
Anti-Histones IgG  
Anti-nRNP/Sm IgG  
Anti-SS-B IgG  
Anti-SS-A IgG  
TGA (Anti-Tg)  
Anti-TPO  
TRAb  
TMA  
ICA  
IAA (Anti Insulin)  
GAD 65  
Anti-IA2  
Anti-tTG IgA  
Anti-tTG IgG  
\*DGP IgA  
\*DGP IgG  
\*Anti-ZnT8  
Anti-MPO IgG  
\*Anti-PR3 IgG  
\*Anti-GBM IgG  
\*Anti-Cardiolipin IgG  
\*Anti-Cardiolipin IgM  
\*Anti-Cardiolipin IgA  
\*Anti-Cardiolipin screen  
\*β<sub>2</sub>-Glycoprotein I IgG  
\*β<sub>2</sub>-Glycoprotein I IgM  
\*β<sub>2</sub>-Glycoprotein I IgA  
\*β<sub>2</sub>-Glycoprotein I screen

## Hypertension

Direct Renin  
Aldosterone  
Angiotensin I  
Angiotensin II  
Cortisol  
ACTH

## Immunoglobulins

IgM  
IgA  
IgE  
IgG

## Tumor Markers

AFP  
CEA  
Total PSA  
f-PSA  
CA 125  
CA 15-3  
CA 19-9  
PAP  
CA 50  
CYFRA 21-1  
CA 242  
CA 72-4  
NSE  
S-100  
SCCA  
TPA-snibe  
ProGRP  
HE4  
HER-2  
PIVKA-II

## Infectious Disease

HBsAg  
Anti-HBs  
HBeAg  
Anti-HBe  
Anti-HBc  
Anti-HBc IgM  
Anti-HCV  
Syphilis  
Anti-HAV  
HAV IgM  
\*HEV IgG  
\*HEV IgM  
HIV Ab/Ag Combi  
Chagas  
HTLV I+II  
H.pylori IgG  
H.pylori IgA  
H.pylori IgM  
2019-nCoV IgG  
2019-nCoV IgM  
SARS-CoV-2 S-RBD IgG  
SARS-CoV-2 Neutralizing Antibody  
SARS-CoV-2 Ag  
Monkeypox Virus Ag  
Dengue Virus IgG  
Dengue Virus NS1  
\*Dengue Virus IgM  
\*Chlamydia Pneumoniae IgG  
\*Chlamydia Pneumoniae IgM  
\*Mycoplasma Pneumoniae IgG  
\*Mycoplasma Pneumoniae IgM

## Veterinary Testing

\*cTSH  
\*cTT4  
\*vFT4

## Glyco Metabolism

C-Peptide  
Insulin  
GAD 65  
Anti-IA2  
ICA  
IAA (Anti Insulin)  
Proinsulin  
\*Glucagon  
\*Anti-ZnT8

## Cardiac

CK-MB  
Troponin I  
Myoglobin  
hs-cTnI  
hs-CRP  
H-FABP  
NT-proBNP  
BNP  
D-Dimer  
Lp-PLA2  
MPO  
HCY  
\*hs-cTnI (STAT)  
\*NT-proBNP (STAT)  
\*Myoglobin (STAT)  
\*D-Dimer (STAT)

## Coagulation Markers

D-Dimer  
TAT  
TM  
PIC  
tPAIC

## Metabolism

Pepsinogen I  
Pepsinogen II  
Gastrin-17  
GH (hGH)  
IGF-I  
IGFBP-3

## Prenatal Screening

AFP (Prenatal Screening)  
free β-HCG  
PAPP-A  
free Estriol

## Anemia

Vitamin B12  
Ferritin  
Folate (FA)  
EPO  
RBC Folate

## Drug Monitoring

Digoxin  
CSA (Cyclosporine A)  
FK 506 (Tacrolimus)

## Bone Metabolism

Calcitonin  
Osteocalcin  
25-OH Vitamin D  
Intact PTH  
β-CTx  
total P1NP

\*Available soon

# Technical Specifications

## Main Features

- Throughput: up to 450 T/H (Single module)
- Sample expansion available
- Integrated wash liquid preparation
- Up to 2000 walk-away tests
- Modular Expanding Flexibility:
  - \*Capable to integrated several modules
  - \*Capable to link with Laboratory Automation System (TLA/LAS)

## Reagent Loading

- 30 reagent positions on board with no-pause loading/unloading
- Double temperature mode ensures working temperature at 8°C-12°C and storage temperature at 2°C-8°C
- RFID reading all information of reagent
- Indicator light available, real-time status monitoring

## Sample Loading

- Up to 112 sample positions (412 with expansion)
- No-pause loading/unloading, STAT available
- Indicator light available, real-time status monitoring
- Barcode recognition: Barcode reader available
- Sample editing mode: Lis connection, barcode recognition, manual editing

## Reagent Features

- MAGLUMI® reagent kits are compatible with all MAGLUMI® analyzers
- Free calibrators and internal controls included
- 10 points master curve, 2-points re-calibration
- RFID tag storing all information of reagents
- Storage temperature 2°C-8°C

## Reaction System

- Single cuvette with five-sided heating at 37.0°C ( $\pm 0.3^\circ\text{C}$ ) incubation, ensuring accurate, quick and uniform incubation
- Non-contact mixing with different modes before incubation, ensuring sufficient reaction

## Tip Storage

- Up to 384 TIPS loaded one time
- Intelligent loading technology, continuous loading, real-time reserve monitoring

## Sampling System

- New generation pipetting technology realizes lower volume
- Filtered TIP avoids aerosol pollution
- Liquid level detection, clot detection, prevent bubble interference, collision detection, wash automatically

## Consumable System

- Single reaction cup design, no-pause loading/unloading
- Starters: 1.5 L of Starter 1 and Starter 2
- Wash liquid: Up to load 140 L at one time automatically
- Indicator light monitors real-time consumable quantity

## Washer

- Intelligent magnetic field design ensures excellent separation
- Three independent non-contact magnetic microbeads vortex cleaning technology
- Resuspension washing mode efficiently reduces non-specific binding and improves sensitivity
- Independent washing unit for waste liquid needle can completely wash without residue
- Integrated auto and manual preparation of wash liquid

## Measuring Chamber

- High-sensitivity and low-noise photomultiplier tube (PMT)
- Heating and cooling bidirectional temperature control function included
- Original light pollution isolation technology prevents light pollution and ensures accurate and reliable results

## Software System

- Friendly software UI design, humanized instrument operation procedure
- Real-time status display for each test procedure
- Self-recovery function make sure the analyzer running smoothly without unnecessary manual intervention
- Bidirectional Snibelis™ connection by TCP/IP and COM Port
- Supporting SnibeLinker™ remote diagnosis system

## Dimensions & Weight

- Dimensions: 148.2\*94\*155 cm
- Weight: 450 kg

MAGLUMI®, Snibelis™ and SnibeLinker™ are trademarks of Snibe.  
All other product names and trademarks are the property of their respective owners.



Shenzhen New Industries Biomedical Engineering Co., Ltd.  
(SNIBE Co.,Ltd.)

No.23, Jinxiu East Road, Pingshan District, 518122 Shenzhen,  
P.R. China

Tel: +86 755 26501514

Email: sales@snibe.com

Fax: +86 755 26654850

Web: www.snibe.com

Follow us on

