

MAGLUMI X8

Fully Automatic Chemiluminescence Immunoassay (CLIA) System



**New
600T/H**

The Fastest CLIA Solution

www.snibe.com
sales@snibe.com

MAGLUMI X8

Chemiluminescence Immunoassay (CLIA) System

Technical Specifications

Reagent Features

- Flash chemiluminescence label-ABEI, with high sensitivity and long stability
- Magnetic Microbeads separation, fast and efficient

Main Features

- Throughput: up to 600 tests/hour (Single module)
- Time to first result: 15 minutes
- 24 hours ready to use
- Up to 2800 walk-away tests
- Modular Expanding Flexibility:
 - *Capable to integrated several modules including Snibe Immunoassay, biochemistry and ISE module
 - *Capable to link with Laboratory Automation system (TLA/LAS)

Sample Loading

- Up to 300 sample positions
- Continuous loading, STAT available
- Auto remeasuring function
- Sample editing mode:
 - Lis connection, Barcode recognition, Auto named, Manual editing

Reagent Loading

- 42 reagent positions on board
- Continuous loading
- RFID technology
- 24-hour refrigerated
- Working Temp. 8°C-12°C, Storage Temp. 2°C-8°C

Reagent Needle

- Titanium needle for crushproof
- Teflon coated for carry-over prevention
- Dual-arm design to pipette different reagents simultaneously
- Liquid level detection, Collision detection
- Probe depth adjustment automatically

Reagent Integral

- Ready to use, no pretreatment required
- Calibrators and internal controls included
- RFID tag storing all info of reagent
- 2-point re-calibration
- Calibration stability: up to 4 weeks
- Storage temperature: 2°C-8°C

Sampling System

- Using disposable TIPS
- One pipetting for multiple tests
- Clot detection
- Liquid level detection
- Bubble detection
- Collision detection

Reaction Disk

- Incubating 252 cuvettes simultaneously
- Stable 37.0°C incubation
- Non-contact mix technology

Tip Storage

- Up to 576 TIPS loaded one time (6 boxes)
- Intelligent loading technology, continuous loading, real-time reserve monitoring

Cuvette Storage

- Single cup design
- Up to 2912 cuvettes loaded one time (16 boxes)
- Intelligent loading technology, continuous loading, real-time reserve monitoring

Washer

- 4-step washing technology, high speed single channel design
- Intelligent magnetic field design ensuring excellent separation
- Non-contact Magnetic Microbeads suspension technology

Software System

- Bidirectional LIS connection by TCP/IP and COM Port
- Supporting SnibeLinker remote diagnosis system

Dimensions Weight

- Input: AC 100-240V,50/60Hz
- Dimensions and Weight:192*118*150 (cm), 670Kg



Shenzhen New Industries Biomedical Engineering Co., Ltd.
(SNIBE Co., Ltd)

21st Floor, Block A, Building 1, Shenzhen Software Industry Base,
No. 1008, Keyuan Road, Nanshan District, Shenzhen 518000 CHINA

Tel: +86 755 26501514

Email: sales@snibe.com

Fax: +86 755 26654850

Web: www.snibe.com

Follow us on

